

GP Batteries

Product Specification

Model No.: GPPB16GS

Description : 2-5 Hours Rapid Charger
 Input Power : 8W
 Input Voltage : AC100-240V 50/60Hz
 Output Voltage : DC3.2V 1050mA
 Application : For charging 2 or 4 pcs NiMH AA batteries; 2 pcs NiMH AAA batteries
 Charging Current and Trickle Charging Current :

Charging current (mA) NiMH			Trickle charging current (mA) NiMH		
AA		AAA	AA		AAA
2 pcs	4 pcs	2 pcs	2 pcs	4 pcs	2 pcs
1050±10%	525±10%	525±10%	105±10%	105±10%	52.5±10%

Charging Time :

Type	Size	Battery	Time (mins)	
			2 pcs	4 pcs
GP NiMH	AA	2500 series	~170	~365
		2300 series	~140	~300
		2100 series	~130	~270
		2000 series	~125	~255
		1800 mAh	~115	~235
		1600 mAh	~100	~210
	AAA	950 series	~130	-
		850 mAh	~120	-
		800 mAh	~100	-
		750 mAh	~95	-
		700 mAh	~90	-

Termination Methods : - ΔV -5mV; Safety timer : 2 cells - 200 mins, 4 cells - 400 mins
 MTBF : 30000 hours (at ambient temperature 25°C)
 Operating Temperature : 5°C to 45°C
 Storage Temperature : -20°C to 65°C
 Charge Indicator : Red LED ON - charging AA/AAA in process
 Green LED ON - full charge & trickle charge
 FLASH - wrong / damage / short circuit / primary battery detected
 Dimensions : 115.5 (L) X 69.5 (W) X 31.9 (T)mm
 Approval : GS and CE
 Warranty Period : 12 months from ex-factory date.

